



### Yale GP15-35MX

Diesel / Dual Fuel / LPG EFI / 1.5T - 3.5T Capacity

Standard Electronic 1-Speed

Height with Mast Lowered (Standard)	1995mm – 2140mm
Height of Overhead Canopy	2181mm – 2185mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	2620kg – 4770kg
Ground Clearance (At Lowest Point)	110mm – 140mm



### Yale GDP/GLP20-35VX

Diesel / 2.0T – 3.5T Capacity

Standard Electronic 1-Speed  
Techtronix 100 1-Speed / Techtronix 200 2-Speed

Height with Mast Lowered (Standard)	2170mm – 2195mm
Height of Overhead Canopy	2181mm – 2185mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	3623kg – 4754kg
Ground Clearance (At Lowest Point)	107mm – 132mm



### Yale GDP/GLP40-55VX

Diesel / LPG / 4.0T – 5.5T Capacity

Techtronix 100 1-Speed / Techtronix 200 2-Speed

Height with Mast Lowered (Standard)	2171mm – 2215mm
Height of Overhead Canopy	2258mm – 2300mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	6264kg – 7811kg
Ground Clearance (At Lowest Point)	151mm – 194mm



### Yale GP135-155VX

Diesel / Petrol / LPG / 6.75T – 7.75T Capacity

Techtronix 332 3-Speed

Height with Mast Lowered (Standard)	3740mm
Height of Overhead Canopy	2549mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	8922kg – 9435kg
Ground Clearance (At Lowest Point)	146mm



### Yale GP/GDP80-90VX

Diesel / LPG / 8.0T – 9.0T Capacity

Techtronix 332 3-Speed

Height with Mast Lowered (Standard)	3462mm – 3962mm
Height of Overhead Canopy	2549mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	11,259kg – 12,250kg
Ground Clearance (At Lowest Point)	173mm



### Yale GDP80-160DC

Diesel / 8.0T – 16T Capacity

Hydro-Dynamic 3-Speed

Height with Mast Lowered (Standard)	4155mm – 4466mm
Height of Overhead Canopy	3015mm – 3064mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	12,413kg – 20,119kg
Ground Clearance (At Lowest Point)	178mm – 248mm



**Yale MR14-25**

Electric / 2.0T Capacity

Height with Mast Lowered (Standard)	2195mm
Height of Overhead Canopy	2175mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	3615kg
Ground Clearance (At Lowest Point)	65mm



**Yale FB15-35RZ**

Electric / 1.5T – 3.5T Capacity

Height with Mast Lowered (Standard)	1995mm – 2140mm
Height of Overhead Canopy	2070mm – 2140mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	3200kg – 5700kg
Ground Clearance (At Lowest Point)	85mm – 140mm



**Yale MP20**

Electric / 2.0T Capacity

Fork Width (Outside Dimension)	520mm – 670mm
Fork Length	1125mm – 1171mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	530kg
Lowered Height	83mm



**Yale MSW025-030F**

Electric / 1.2T – 1.4T Capacity

Fork Width (Outside Dimension)	520mm – 670mm
Fork Length	1067mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	170kg
Lowered Height	83mm



**Forks 4 U Pallet Jack MB25Q**

Hand Pallet Jack / 2.5T Capacity

Fork Size	685mm x 1150mm
Minimum Fork Height	75mm



**Yale MSW025-030F**

Electric / 1.2T – 1.4T Capacity

Fork Width (Outside Dimension)	520mm – 670mm
Fork Length	1067mm
Unladen Weight (Standard Tread / Mast / Forks etc.)	170kg
Lowered Height	83mm

**QUALITY, STYLE AND EXCEPTIONAL VALUE**

Our Forks 4 U Sales Dept has a range of forklifts, pallet trucks and walker-stackers which will be sure to meet all your company needs and requirements. Forks 4 U offer lifting equipment with extended warranties applying to all lifting units from light-handling to heavy lifting. We also stock a range of refurbished equipment at competitive prices.